

25M GAS DRYER VALVES & COILS



25M01A-100

Clothes dryer gas valves combine pressure regulator main and redundant solenoids for hot surface ignition dryers.

FEATURES

- Compact split coil design
- Inlet/outlet screen
- Field-adjustable regulator
- Replaceable operating coils (no gas interruption)
- Outlet pressure tap
- Both models packaged with the most popular main burner orifices to replace many OEM models
- Replacement coils available for most popular models
- Single or complete coil sets

SPECIFICATIONS

Type of Gas Natural or LP gas (conversion kit included)
 Pressure Regulator Setting Nat. Gas: 2.8" to 5.4"W.C., LP Gas: 8.5" to 12.0"W.C.
 Operating Ambient Temperature..... 32° to 155°F
 Max. Pressure Rating 1/2" PSI (14.0" WC)
 Electrical 120 VAC, 60 Hz, .06 amps
 1" P.D. Capacity 40,000 BTU/HR

25M GAS DRYER VALVES & COILS

COIL VOLTAGE	OUTLET FLOW DIRECTION	INLET/OUTLET SIZE	REGULATOR ADJUSTMENT RANGE	MOUNTING	MODEL NUMBER	ITEM NUMBER
120 VAC	Right Angle Left	3/8" NPT X 11/32"	Nat. Gas: 2.8" to 5.4"W.C. LP Gas: 8.5" to 12.0"W.C. (Conversion Kit Included)	Control may be mounted in the following positions: horizontal, vertical or 90° of horizontal. Do not mount upside down.	25M01A-100	25M01A100
120 VAC	Right Angle Right	3/8" NPT X 11/32"	Nat. Gas: 2.8" to 5.4"W.C. LP Gas: 8.5" to 12.0"W.C. (Conversion Kit Included)	Control may be mounted in the following positions: horizontal, vertical or 90° of horizontal. Do not mount upside down.	25M01A-101	25M01A101



F91-3889



F91-3890

2500 SERIES REPLACEMENT GAS VALVE COILS

FEATURES

- Easy installation of replacement coil assemblies
- Available for most popular models
- Single or complete coil sets

PARTS AND ACCESSORIES

APPLICATION	DESCRIPTION	OEM	MODEL NUMBER	ITEM NUMBER
25M01A-xxx	120 VAC Coil Replacement for 25M valve individual pack secondary coil	Whirlpool, Electrolux, GE, Maytag, Speed Queen	F91-3889	F0091 388900S1
25M01A-xxx	120 VAC Coil Replacement for 25M valve individual pack booster and holding coil	Whirlpool, Electrolux, GE, Maytag, Speed Queen	F91-3890	F0091 389000S1
25M01A-xxx	Boost/host coil and secondary coil (120 VAC, 60 Hz) for 25M dryer gas valve (includes F91-3889 plus F91-3890 combined)	Whirlpool, Electrolux, GE, Maytag, Speed Queen	F91-4241	F91-4241