Copevap[™] hermetic air-cooled condensing units

Refrigeration condensing units with evaporative condensate pans

- The condensate holding base and discharge line design provide ample holding volume and a quick evaporation rate for condensate removal
- Eliminates the need for electric resistance heaters and external piping to drains
- High-efficiency compressor and condenser in a compact package



Features

Copeland[™] hermetic compressor and heavy dutyunit bearing fan motor

Larger condensate holding base

Fan guard standard

Compact and narrow base design All models rated up to 100°F ambient

Copper-nickel discharge tubes

Modular components

Benefits

Reliability High energy efficiency Low sound and vibration

Quick evaporation rate for condensate removal


Cost savings (No need to add parts)


Application flexibility

Corrosion resistance


Replacement serviceability








E base (3/4 HP and smaller)





Dimensions

Copevap Base	Length	Width	Water Storage
Р	19.9"	11.0"	79 oz
В	24.0"	16.1"	160 oz
E	16.0"	14.3"	84 oz
Т	19.0"	8.3"	46 oz

Product Information

Horsepower

1/6 – 1 ¼ HP

Temperature Applications

Low/Medium/Extended Medium/High

Refrigerants

R-134a, R-404A, R-448A, R-449A, R-450A, R-513A, R-290

Applications

Reach-Ins, display cases, under-counter, sandwich, salad and food prep tables, and milk or juice coolers

2017ECT-34 (12/17) Emerson, Copeland and Copevap are trademarks of Emerson Electric Co. or one of its affiliated companies. ©2017 Emerson Climate Technologies, Inc. All rights reserved.

Emerson.com

EMERSON. CONSIDER IT SOLVED.